# ECO1900UPOT

Product description: upright 1900 litre rectangular baffled storage tank, manufactured from WRAS approved polymer





















| Product Information |        |       |        |            |                   |
|---------------------|--------|-------|--------|------------|-------------------|
| Height              | Length | Width | Weight | Outlets    | Lids              |
| 1520mm              | 2190mm | 720mm | 120kg  | 2 x 2" BSP | 2 x 14" screwdown |

Sizes approximate, owing to shrinkage Specification subject to change; please call to confirm details

#### PRODUCT NOTES:

- Tank must be sited on level, fully supporting base.
- Additional fittings can be added as and where required without compromising tank's structural integrity.

### **PRODUCT DETAILS:**

- Made from WRAS approved polymer
- Approximate wall thickness: 7mm
- 2 x 14" non-vented lids as standard
- 2 x 2" brass threaded outlets moulded into the tank
- Central baffles

#### **BENEFITS:**

- Suitable for internal and external use
- Frost-proof; plastic will not crack in cold
- Plastic meets the requirements of BS 6920-1:2000
- Plastic will not contaminate water
- Slimline shape, ideal when space is limited
- Holds shape when full of water
- Robust, heavy duty product; industrial strength
- Rotationally moulded for strength & durability
- 2 year warranty against manufacturing defects

## **OPTIONAL EXTRAS:**

- Brass tap
- Brass isolation valve
- By-law 30 kit
- Ball cock and float valve
- Tank connectors
- Stainless steel insert
- 16" non-vented lids
- 1" or moulded blank (no outlet)



