

# ECO1275PILBLK

Product description: 1275 litre pillar tank with multiple outlets, suitable for internal or external use



## Product Information

Height	Width	Depth	Weight	Outlets	Lid
1765mm	1130mm	660mm	75kg	1 x 3/4", 1 x 1 1/2", 1 x 2" BSP	14" screw-down

### PRODUCT NOTES:

- Tank must be sited on a level, fully supportive base leaving a gap of at least 50mm from walls or other tanks
- Multiple outlets. Raised tap connection allows containers to be filled. Lower outlets allow tank to be completely drained
- Outlets not drilled unless requested

Sizes approximate, owing to shrinkage

### PRODUCT DETAILS:

- Made from virgin polymer
- Approximate wall thickness: 6-7mm
- Vented 14" screw-down lid as standard
- 3/4" raised brass threaded outlet
- 1 1/2" threaded outlet moulded into tank on left side
- 2" threaded outlet moulded into tank on right side

### OPTIONAL EXTRAS:

- Brass tap
- Brass isolation valve with hose connector
- Upgrade to 16" screw-down lid
- Tank connectors
- Stainless steel inserts
- Ball cock and float valve
- Non-vented lid

### BENEFITS:

- Suitable for internal and external use
- Frost proof; will not crack in the cold
- Robust, heavy duty product; industrial strength
- Modern, minimalist pillar design
- Small footprint maximises capacity when space is limited
- Tanks can be connected together using bottom outlets
- Opaque plastic reduces algae growth in sunlight
- Rotationally moulded for strength and durability
- 2 year warranty against manufacturing defects



Scan to view our full range of water tanks



Etills Ltd,  
Unit 1 Whiting Way,  
Melbourn,  
Royston,  
SG8 6NA



Call 01763 261781