ECO825PILWATERBUTT

Product description: 825 litre pillar tank with multiple outlets, manufactured in a variety of colours



Product Information					
Height	Width	Depth	Weight	Outlets	Lid
1800mm	825mm	630mm	40kg	1 x ¾" & 2 x 1" BSP	9" screw-down

PRODUCT NOTES:

Sizes approximate, owing to shrinkage

- Tank must be sited on a level, fully supportive base leaving a gap of at least 50mm from walls or other tanks
- Use hole-cutter to fit rainwater diverter or overflow pipe where required
- Connect a tap to the raised connection to fill a watering can
- Use brass isolation valve to connect irrigation hose to either of the lower outlets and water the garden at the turn of a lever
- Fixing brackets and instructions supplied
- Outlets not drilled, unless requested.

PRODUCT DETAILS:

- Available in a variety of colours to suit location
- Made from virgin polymer
- Approximate wall thickness: 6-7mm
- Vented 9" screw-down lid as standard
- ³/₄" raised brass threaded outlet
- 2 x 1" brass threaded outlets one on each side

BENEFITS:

- Suitable for internal and external use
- Frost proof; will not crack in the cold
- Robust, heavy duty product; industrial strength
- Modern, minimalist pillar design
- Small footprint maximises capacity when space is limited
- Tanks can be connected together using bottom outlets
- Opaque plastic reduces algae growth in sunlight
- Rotationally moulded for strength and durability
- 2 year warranty against manufacturing defects

OPTIONAL EXTRAS:

- Brass tap and/or Brass isolation valve with hose connector
- Tank connectors
- Downpipe diverter or filter diverter
- Basket filter
- Fresha tabs
- Upgrade to 14" or 16" lid
- Non vented lid
- Heavy-duty restraining kit



Etills Ltd, Unit 1 Whiting Way, Melbourn, Royston, SG8 6NA

Call 01763 261781